



PRODUCT CODE

FDMS-BB (Bullnose Meeting Stile Seals)

DESCRIPTION

Aluminium meeting stile assembly for proprietary double action fire door assemblies.

APPLICATION

An aluminium meeting stile sealing system designed specifically for high performance smoke and sound containment for pairs of nom. 47mm fire doors.

KEY FEATURES

- New modern and aesthetic appearance.
- Incorporates intumescent fire and smoke sealing technology
- Improves acoustic performance.
- Can be used to upgrade existing fire doors.
- Easy installation.
- Sold as complete assembly incorporating two identical aluminium sections and PVC encased intumescent seals with elastomeric smoke and acoustic fins.

MATERIALS

Anodised aluminium astragals with integral high performance intumescent fire seals encapsulated in a rigid, flame retardant PVC outer casing, with a co-extruded single asymmetric smoke and acoustic fin.

GAP SIZE

Minimum 2.5mm — Maximum 5mm

SIZES

Standard Lengths 2135mm, 2440mm, 3050mm, 3500mm

FINISH

- Clear anodised finish with silver colour fire seal and black offset fin.

FIXING

The Lorient FDMS-B Bullnose Stiles come complete with the aluminium sections and intumescent fire and smoke seals. Simply cut to length, screw aluminium sections onto the respective door leaves and insert the intumescent seals using aggressive self adhesive backing tape.

APPROVAL/S

- AS1530/4 fire tests with proprietary fire door assemblies.
- Can be considered deemed to satisfy to BCA specification C3.4 for use with smoke doors (when fitted to compliant door leaf).
- Can provide acoustic ratings to AS1191 and AS1276 in conjunction with other Lorient Integrity seals.

SPECIFICATIONS

Fit Lorient FDMS-BB meeting stiles to pairs of doors for proven fire, smoke and acoustic containment.

