



PRODUCT CODE

IS4010, IS4015, IS4020, IS4025

DESCRIPTION

Heavy duty, low profile threshold plates.

APPLICATION

These threshold plates are used in conjunction with other Lorient Integrity™ seals to prevent rain, draught and smoke penetration. Their low profile ensures compliance with the 'access for people with disability' requirements, particularly for wheelchair traffic.

KEY FEATURES

- Supplied with PVC bedding pads to eliminate vibration and noise.
- Durable, anodised aesthetic finish.
- 6mm, low profile design complying with AS1428/1 and BCA D3.
- Suitable for wheelchair traffic.
- Helps prevent rain infiltration when used in conjunction with a Lorient Integrity™ 3000 or 8000 series door bottom seal.

USE WITH

Used in conjunction with a Lorient Integrity™ 7000 series perimeter seal and an 8000 series automatic door bottom seal to provide a total door sealing solution.

MATERIALS

Extruded and anodised aluminium.

SIZES

Standard Lengths 1000mm, 2250mm
Also available in 250mm increments:
 1000mm to 5000mm
Seals can be cut on-site for exact dimensions. Order length wider than door opening to provide a neat detail at door frame.

FINISH

- Silver anodised aluminium.
- Bronze anodised aluminium.

FIXING

Appropriate fixing screws are supplied. Alternatively, can be fastened with builders adhesive for concealed fixing.

APPROVAL/S

- AS1530/4 fire tests with proprietary fire door assemblies.
- Complies with AS1428/1 (Design for access and mobility).
- Conforms to Building Code of Australia BCA D3 (Access for people with disabilities).

SPECIFICATIONS

Lorient Integrity™ IS4010/IS4015/IS4020/IS4025 threshold plate fitted to the sill under the door.

