



PRODUCT CODE

IS4220si

DESCRIPTION

Heavy duty, acoustic and weather resistant threshold plate.

APPLICATION

The IS4220si threshold plate is suitable for outward opening doors to prevent rain, draught, light and noise penetration.

KEY FEATURES

- Supplied with vinyl bedding pads to eliminate vibration and noise.
- Durable anodised finish.
- The high performance silicone rubber compression seal helps resist rain, light, dust and noise infiltration.

USE WITH

Used in conjunction with a Lorient Integrity® 7000 series perimeter seal to provide a total door sealing solution.

MATERIALS

Extruded and anodised aluminium with high performance silicone compression seal and moulded PVC bedding pads.

SIZES

Standard Lengths 1000mm, 2250mm
Also available in 250mm increments: 1000mm to 5000mm
 Threshold plates can be cut on-site for exact dimensions.
 Order length wider than door opening to provide a neat detail at door bottom.

FINISH

- Silver anodised aluminium with grey silicone rubber gasket and vinyl bedding pads.
- Bronze anodised aluminium with black silicone rubber gasket and vinyl bedding pads.

FIXING

Appropriate fixing screws and plugs are supplied. Alternatively, can be fastened with builders adhesive for concealed fixing.

APPROVAL/S

- AS1530/4 fire tests with proprietary fire door assemblies.

SPECIFICATIONS

Lorient Integrity™ IS4220si threshold plate fitted to the sill under the door.

