

## PRODUCT CODE

**IS5110, IS5115, IS5120, IS5130**

## DESCRIPTION

Heavy duty sweep action brush seals.

## APPLICATION

These brush seals are designed to be used around the head and jambs, door bottoms and meeting stiles of single or double swing doors, revolving, tilt-up and roller doors. These seals protect against draught and dust, insects and weather penetration.

## KEY FEATURES

- Slim-line, angled, aesthetically designed carriers avoid dust build-up.
- Suitable for clean room applications.
- Suitable for disabled access.
- Easily installed without removing the door.

## USE WITH

Used in conjunction with a Lorient Integrity™ 4000 Series threshold plate for a complete door sealing solution.

## MATERIALS

Extruded and anodised aluminium, with nylon brush filaments.

## GAP SIZE

<b>IS5110</b>	Minimum 10mm—Maximum 13mm
<b>IS5115</b>	Minimum 13mm—Maximum 19mm
<b>IS5120</b>	Minimum 19mm—Maximum 25mm
<b>IS5130</b>	Minimum 40mm—Maximum 50mm

## SIZES

<b>Standard Lengths</b>	1000mm, 2250mm
<b>Also available in</b>	250mm increments: 1000mm to 3000mm Seals can be cut on-site for exact dimensions.

## FINISH

- Silver anodised aluminium with black brush filaments.
- Bronze anodised aluminium with black brush filaments.

## FIXING

Brush seals can be adhered to desired surface prior to screw-fixing. Fixing screws and aggressive backing tape are supplied.

## APPROVAL/S

- Independent tests demonstrating over 100,000 open and close cycles.

## SPECIFICATIONS

Lorient Integrity™ IS5110/IS5115/IS5120/IS5130 fitted to the perimeter/bottom/meeting stile of the door leaf.

