


**PRODUCT CODE**
**IS7025si**
**DESCRIPTION**

Medium duty door perimeter seal.

**APPLICATION**

The IS7025si door frame perimeter seals are designed to be fitted to an existing door stop, around the head and jambs of single swing doors.

**KEY FEATURES**

- Slim-line, aesthetic design.
- Pre-drilled and slotted fixing holes provide for adjustable installation.
- Triple-finned seal, reduces sound and air leakage.
- Easy to install flexible cover strip for concealed fixings.
- Silicone (si) gasket standard for fire & smoke applications.
- Easily installed without removing the door.
- Suitable for use on steel and timber door frames.

**USE WITH**

Used in conjunction with a Lorient Integrity™ 8000 series automatic door bottom seal and a 4000 series threshold plate to provide a total door sealing solution.

**MATERIALS**

An extruded and anodised aluminium profile combined with a cover strip and a silicone rubber flexible gasket.

**GAP SIZE**

Minimum 0mm - Maximum 7mm

**SIZES**
**Door Sets**

Single	1 x 1000mm, 2 x 2100mm
Long Single	1 x 1000mm, 2 x 2750mm
Double	3 x 2100mm
Long Double	1 x 2100mm, 2 x 2750mm

**Standard Lengths** 1000mm, 2250mm

**Also available in** 250mm increments: 1000mm to 5000mm

**FINISH**

- Silver anodised aluminium with grey silicone gasket and grey cover strip.
- Bronze anodised aluminium with black silicone gasket and black cover strip.

Other finishes available to special order.

**FIXING**

Self-drilling metal and timber fixing screws are supplied. Fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately. A decorative cover strip is supplied to conceal fixings.

**APPROVAL/S**

- AS1530/4 fire tests with proprietary fire door assemblies.
- Acoustic ratings to AS1191 and AS1276 in conjunction with other Lorient Integrity™ seals.

**SPECIFICATIONS**

Lorient Integrity™ IS7025si fitted to the perimeter of the door frame.

