



PRODUCT CODE
IS7060si

DESCRIPTION

Medium duty meeting stile seal for pairs of doors.

APPLICATION

An astragal seal used with either plain or rebated meeting stiles on double doors where only one door leaf is active. It provides an excellent acoustic, cold smoke, light, dust and weather seal.

KEY FEATURES

- Thin fixing leg allows this seal to be face-fixed to the door (no rebating required).
- Provides an aesthetic appearance when doors are closed as the aluminium profile conceals the sealing gasket.

USE WITH

We recommend the IS7060si meeting stile seal be fitted with a Lorient Integrity™ 7000 series perimeter seal and 8000 series automatic door bottom seal.

MATERIALS

An extruded and anodised aluminium profile combined with a silicone rubber flexible gasket.

GAP SIZE

Minimum 2.5mm - Maximum 12.0mm

SIZES

Standard Lengths 2250mm, 3000mm
Also available in 250mm increments: 2000mm to 3500mm

FINISH

- Silver anodised aluminium with grey silicone gasket.
 - Bronze anodised aluminium with black silicone gasket.
- Other finishes available to special order.

FIXING

Fixing screws are supplied. Fixing holes are pre-drilled and countersunk. This seal can be face-fixed and no rebating is necessary. If required, the leg of the aluminium profile can be cut away to make way for locks and latches.

APPROVAL/S

- Can be considered deemed to satisfy to BCA Specification C3.4 for use with smoke doors (when fitted to compliant door leaf).
- Acoustic ratings to AS1191 and AS1276 in conjunction with other Lorient Integrity™ seals.

SPECIFICATIONS

Lorient Integrity™ IS7060si fitted to the meeting stile of a pair of doors.

