



PRODUCT CODE

IS7070si

DESCRIPTION

Medium duty meeting stile and door perimeter seal.

APPLICATION

The IS7070si astragal seal is designed to be fitted to plain or rebated meeting stiles of double doors or double action doors. Two IS7070si seals are installed onto one door stile, allowing a space for a latch between the seals if required.

KEY FEATURES

- Slim-line, aesthetic design.
- The aluminium carrier can be cut to accommodate a latch bolt plate (if required), thereby maintaining a continuous seal.
- Twin-finned, high performance silicone seal provides excellent smoke and acoustic properties.
- Easy to install, rigid cover strip for concealed fixings.
- Easily installed without removing the door.
- Suitable for use on steel and timber doors.

USE WITH

Used in conjunction with a Lorient Integrity™ 7000 series perimeter seal, dependent on door type.

MATERIALS

An extruded and anodised aluminium profile combined with a cover strip and a flexible silicone gasket.

GAP SIZE

Minimum 3mm - Maximum 6mm

SIZES

Standard Lengths 2250mm, 3000mm
Also available in 250mm increments: 1000mm to 5000mm
 Seals can be cut on-site for exact dimensions.

FINISH

- Silver anodised aluminium with grey cover strip and grey gasket.
- Bronze anodised aluminium with black cover strip and black gasket.

FIXING

Fixing screws are supplied. Fixing holes are pre-drilled. A decorative cover strip is supplied to conceal fixings.

APPROVAL/S

- AS1530/4 fire tests with proprietary fire door assemblies (when fitted to door perimeters).
- Can be considered deemed to satisfy to BCA specification C3.4 for use with smoke doors (when fitted to compliant door leaf).
- Acoustic ratings to AS1191 and AS1276 in conjunction with other Lorient Integrity™ Seals.

SPECIFICATIONS

Lorient Integrity™ IS7070si fitted to the meeting stile of a pair of doors.

