


**PRODUCT CODE**
**IS7330si**
**DESCRIPTION**

Adjustable aluminium meeting stile seal and door edge seal for hinged or pivoted frameless glass doors, incorporating high temperature silicone gasket.

**APPLICATION**

Designed to suit frameless glass doors—ranging in thickness from 12mm to 15mm—for ambient/medium temperature smoke containment, along with draught and dust protection. Ideally suited to frameless glass pivot door applications.

**KEY FEATURES**

- Adjustable, anodised aluminium, aesthetic carrier to suit 12mm to 15mm glass doors.
- High performance, flexible silicone rubber gasket to ensure an excellent seal is created, resisting temperatures up to 200°C for 30 minutes.
- Low friction.
- Easy clip-fixed, self-adhesive application.
- Can be used independently for various glass door applications.

**MATERIALS**

An extruded, clear anodised aluminium, two-piece carrier, combined with a high performance, finned silicone rubber gasket.

**GAP SIZE**

Dependent upon application.

**SIZES**

**Standard Lengths** 2250mm

**Also available in** 250mm increments: 1000mm to 5000mm.

**FINISH**

- Clear anodised aluminium with grey silicone finned gasket.

**FIXING**

Simply clips onto the door edge and secured into position with high temperature aggressive tape provided. Detailed fixing instructions are supplied.

**SPECIFICATIONS**

Lorient IS7330si fitted to the edges of glazed door openings.

